



## PS100

---

**Power Supply**  
**Variable AC / DC**

# Power Supply Variable AC / DC

## Introduction

Weis is a specialist company with over 40 years of experience in the commissioning, testing & maintenance of switchgear and power network fault monitoring within the Power Utility Industry.

The **PS100** Power Supply is a variable power source, mainly for Switchgear Testing and is an instrument intended for use in Power Station, Substation & industrial environments.

As Station Batteries should not be used or interfered with, the **PS100** provides an ideal alternative power source for testing the breaker, as well as for minimum operating voltage testing of breaker coils, as laid out in international rules and regulations.

Also available within our range of switchgear test equipment:

- ▶ **SA100**, Switchgear Analyser

---

- ▶ **SA100R**, Switchgear Analyser

---

- ▶ **SA100RS**, Breaker Analyser

---

- ▶ **SA100s**, Breaker Timing Test Set

---

- ▶ **MM100**, Micro-ohm Meter

---

- ▶ **RT100**, Secondary Injection Relay Test Set

---

- ▶ **SA200**, Automated Factory Test System

---




## Specifications

### OUTPUT

**AC Power:** 0 to 280V AC  
30A peak  
**DC Power:** 0 to 280V DC  
30A peak  
**Ripple:** < 2%

### OUTPUT CHARACTERISTICS

#### DC Breaker Coils:

No-load Voltage	Current	Load Dependency
24V	10A	< 5%
48V	10A	< 3%
55V	10A	< 3%
110 / 120V	8A	< 2%
220 / 240V	3A	< 2%
280V	1.5A	< 2%

#### AC Breaker Coils:

Voltage Range	Load Current	Load Interval
0-280V AC	10A max.	30min max.

#### DC Spring Charging:

Open Circuit Voltage	Current	Load Voltage	Max. Load Interval
24V	20A	20V	30s
48V	15A	40V	60s
55V	20A	40V	30s
110 / 120V	15A	95V	40s
220 / 240V	10A	190V	30s



### MEASUREMENT

**Readout:** 3 digit backlight LCD display  
**Resolution:** 1V steps  
**Displayed Values:** AC Voltage  
AC Current  
DC Voltage  
DC Current  
**Accuracy:** +/- 1% of displayed value

### OPERATING VOLTAGES

**Fixed Prime Power:** 220 to 240V 50/60Hz  
or  
110 to 120V 50/60Hz  
*Auto-sensing*

### ENVIRONMENTAL

**Operating Temperature:** -20°C to +70°C (-4°F to +158°F)  
**Humidity:** 0 to 97% RH non-condensing  
**Isolation:** 2kV rms for 1 minute  
**Surge Withstand Transient:** To IEC 801-5. 1.2/50µS  
Common Mode: Severity level class 4. Series Mode: Severity level class 3  
**Fast Transient Burst:** To IEC 801-4 level 3  
**RFI Immunity:** To IEC801-3 level 3. 10V/m 26-1000MHz  
**Emissions:** To EN50081-1: 1992



### MECHANICAL DETAILS

**Weight:** > 20Kg  
**Carry Case:** Reinforced aluminium, 340mm x 240mm x 150mm

# Power Supply Variable AC / DC

# PS100



## HEAD OFFICE

**WEIS GMBH & Co. KG**

Kaffeestrasse 4  
28779 Bremen  
Germany  
Tel: +49 (0) 421 606040  
Fax: +49 (0) 421 607066  
Email: WeisGmbHBremen@t-online.de



Room 506, Building 7, No.59, Shennan Road  
Taihong R&D Office Part, Minhang District  
Shanghai China 201108  
Tel / Fax: +86 (0) 21 34635190  
Email: gui.shanghai@hotmail.com

[www.weisgmbh.com](http://www.weisgmbh.com)

## UK OFFICE

**WEIS GMBH & Co. KG**

'Bay Trees' 47 Beltinge Road  
Herne Bay  
Kent CT6 6DA  
UK  
Tel: +44 (0) 1227 749413  
Email: sales@WeisGmbH.com